

High Quality Products

dichtol Metal impregnation and sealing materials

- Reliable impregnation up to 0,5 mm pore size
- Without vacuum and additional machines
- Temp. resistant up to 500°C / 932°F - pressure tested up to 500 bar / 7250 psi
- Highly chemical resistances and easy to apply, usable on the spot



plasticmetal Small and medium metal & casting repairs

- Free mixing ratio by volume or weight
- Short curing times (less than 0,5 hours)
- Machineable like metal, and very good chemical resistance
- High Temperature resistance up to 250° and physical strength & good adhesion



ultrametal Cold welding & metal repair

- Very good adhesion to metals
- Reasonable pot life and nearly no shrinkage
- Machinable like metal
- Very good chemical resistance, no corrosion



moglice ... forms micron - exact

- Enables dynamic elements, e.g. slideways to run easily
- Protects from wear and tear
- Lowers buying as well as running costs



DWH Adjustment coating for machine construction

- Two component sealing
- Aligning and adjusting of machine elements in engineering
- Makes an exact copie of the tool surface



MM1018 Gap compensation for steel & bridge construction

- 100% full-surface gap compensation
- Metallpolymer with high compressive strength
- Gap to a maximum height of 10mm, fully loadable after 24 hours
- No machining required



repacoat Metal protection system

- Corrosion protection
- Protection against aggressive media
- Easy application - molding solutions



Local Distributor:

EleMech
Electrical and Mechanical Solutions

Office N° 1602 Level 16 , JBC 4
Cluster N, Jumeirah Lake Towers
P.O Box – 18333,
Dubai - UAE.

Tel: +971 4 361 4444
Fax: +971 4 360 4427
www.elemech.net
info@elemech.net

DIAMANT Metallplastic GmbH
Hontzlarstr. 12-14
41238 Mönchengladback
Germany